



**FLAG & BANNER FABRIC**

**BANNER**

**PRODUCT CODE**

**S12 / D12**

 DYE DIRECT YES	 DYE PAPER YES	 LATEX NO	 ECO SOLVENT NO	 UV NO	 rPET OPTIONAL	 NO
 YES	 YES	 NO	 NO	 NO	 OPTIONAL	

SPECIFICATION <sup>1</sup>		METRIC	IMPERIAL
MATERIAL	TYPE	Warp-Knit	
	COMPOSITION	100% Polyester	
	DESCRIPTION	Mechanical Stretch	
PROPERTIES	WEIGHT <sup>2</sup>	230 g/sq.m	6,78 oz/sq.yrd
	MAX WIDTH	320 cm	126 inch
	STANDARD ROLL LENGTH	50 m	66 yrd
	RECOMMENDED FIXATION TEMP. <sup>3</sup>	190°C - 210°C Heat Press	374°F - 410°F Heat Press
	SHRINKAGE <sup>3</sup>	<2-3%	
	YELLOWING TEMP. <sup>3</sup>	>210°C	>410°F
	YELLOWING TEMP. TEST	SUPRKC REX-C400, 30s	
APPLICATIONS <sup>3</sup>	Banners		
	Tubular Stretch Frames		
	Sensomatics		
	Table Cloth		

<sup>1</sup> This information should be used as a guide only. Figures are test result averages and should not be used for lawsuits or warranties.  
<sup>2</sup> It is normal for the weight of most products to fluctuate by ±5% on average.  
<sup>3</sup> Users should independently test & determine the product's application & printing suitability, shrinkage, fixation and yellowing temp.

SALES@ORIGINPRINTMEDIA.COM  
**ORIGINPRINTMEDIA.COM**